




NO. 12D630S-2018-A0




LABEL (铭牌):



WIRING DIAGRAM (接线图):




FLOW RATE CURVE (风量曲线):



WEIGUANG®

SPECIFICATION 规格说明
HANGZHOU WEIGUANG ELECTRONIC CO.,LTD.

UNIT 类型	Axial fan motor
MOTOR 电机型式	Three phases motor
MOTOR TYPE 电机型号	YWF12D-630S-137/50-G
VOLTAGE 额定电压 (V)	380
FREQUENCY 频率 (Hz)	50
INPUT POWER 输入功率 (W)	120
CURRENT 电流 (A)	0.33
SPEED 转速 (r/min)	430
AIR FLOW 20Pa 风量 (m³/h)	2930
NOISE 噪音 (dBA)	52
CAPACITOR 电容 (μF/450V)	-
ROTATION 旋转方向	CW ,looking into the end-shield 顺时针, 从端盖端方向看
INSULATION CLASS 绝缘等级	B
MOTOR PROTECTION 电机保护	Thermocontact 135±5℃ 热保护器
TEMPERATURE RISE 温升	75K max 运行温升不超过75K
TYPE OF PROTECTION 防护等级	IP54
OPERATING TYPE 工作定额	S1 连续工作制
AMBIENT TEMPERATURE 适用环境温度	-30℃ +60℃
BEARINGS 轴承型式	Ball bearings 滚珠轴承
MOUNTING TYPE 安装方式	Horizontal or Vertical 垂直或水平安装
ELECTRICAL CONNECTION 电源线	Lead wire Silikon 4G 0.75mm²+2G 0.30mm², Length 100mm in terminal box connected 接线盒 (4芯0.75mm²+2芯0.30mm²线长100mm)
APPROVALS 认证标记	CE
NET WEIGHT/GROSS WEIGHT 净重/毛重	15.0/17.0kg
PACKING 包装	67.0*67.0*25cm

REV.	DESCRIPTION	APPROVED	DATE	DRN.BY	SIGN	DATE	TITLE
				CHD.BY			YWF12D-630S-137/50-G
				ENG.BY			PROJECTION 
				APP.BY			A4 SCALE SHEET: of